


**GROUP 600
ACCESSORIES
MOD. 630/82**



**DAVINCI
VALVES™**

**TECHNICAL
DATA SHEET**
WATER Series

REPAIR CLAMP S.STEEL

**DAVINCI
VALVES™**



**QUALITY
ASSUREMENT**

**DAVINCI
VALVES™**



**PRODUCT QT
ASSUREMENT**

**DAVINCI
VALVES™**



**COMPANY QT
ASSUREMENT**

www.davincivalves.com

18 Dongyu Street, Square One,
11th Floor 1101, Jinjiang District,
Chengdu, Sichuan CHINA

10F/Tower A, Billion Center,
1 Wang Kwong Road, Kowloon Bay
Kowloon HONG KONG

FULL S.STEEL REPAIR CLAMP

Ref.630A / PN 10-16

APPLICATION:

Water, HVAC installations, irrigation, industry, others

WORKING CONDITIONS:

Working Temperature:

- 10 °C - + 120 °C. for EPDM

- 10 °C - + 82 °C. for NBR

GENERAL CHARACTERISTICS:

Size DN50 to DN1000,

working pressure PN10/PN16

Full S.steel ss304


STANDARDS:

Comply with EN545



Materials Specification

Sr.No.	Name	Material
1	Bolt	SS304
2	Lug Plate	SS304
3	Counter Plate	SS304
4	Washer	SS304
5	Nut	SS304
6	Gasket	EPDM/NBR
7	Welding Plate	SS304
8	Band	SS304



Dimensions(mm)

DN	50	80	80	100	100	150	150	200	200	250	250	300	300
OD Range	60-67	88-98	95-105	108-118	115-128	158-172	168-182	217-229	225-240	243-260	270-288	313-336	340-360
Length	150/200	150/200/300	150/200/300	150/200/300	150/200/300	200/300	200/300	200/300	200/300	200/300/450	200/300/450	200/300/450	200/300/450


All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice.

© 2018 DAVINCI VALVES LTD.

www.davincivalves.com info@davincivalves.com +34 616553797 / +86 17340168233
18 Dongyu Street, Square One 11th Floor 1101. Jinjiang District, Chengdu, Sichuan Province, China

"For professionals who wants more"



DAVINCI
VALVES™

www.davincivalves.com