


**GRUPO 600  
ACCESORIOS  
MOD. 601/72**



**DAVINCI  
VALVES™**

# FICHA TECNICA

## WATER Series

**BRIDAS PARA TUBERIA PE/HDPE/PVC MEDIDAS  
GRANDES**

**DAVINCI  
VALVES™**



**QUALITY  
ASSUREMENT**

**DAVINCI  
VALVES™**



**PRODUCT QT  
ASSUREMENT**

**DAVINCI  
VALVES™**



**COMPANY QT  
ASSUREMENT**

[www.davincivalves.com](http://www.davincivalves.com)

18 Dongyu Street, Square One,  
11th Floor 1101, Jinjiang District,  
Chengdu, Sichuan CHINA

10F/Tower A, Billion Center,  
1 Wang Kwong Road, Kowloon Bay  
Kowloon HONG KONG

## UNIVERSAL SADDLES

Ref.601A / PN 10-16

### APLICACIÓN:

Agua, instalaciones de climatización,  
riego, industria, otros

### CONDICIONES DE TRABAJO:

Temperatura de trabajo:

- 10 ° C - + 120 ° C. para EPDM

- 10 ° C - + 82 ° C. para NBR

### CARACTERÍSTICAS GENERALES:

Rango de DN050 a DN400

Recubrimiento curado epoxi en polvo 250 Mic

Rosca BSP / NPT

### ESTANDARES:

Cumple con EN545

Prueba de presión: EN 12266-1.

Cuerpo: 16 bar

| No. | Parte     | Material     |
|-----|-----------|--------------|
| 1   | Cuerpo    | F.Ductil     |
| 2   | Junta     | EPDM         |
| 3   | Banda     | Inox+EPDM    |
| 4   | Tornillos | AC 8.8 Dacro |

| Head<br>DN | Rosca  | Bandas<br>Nº | A   | B   |
|------------|--------|--------------|-----|-----|
| 50-200     | 3/4"   | 1            | 150 | 70  |
| 50-200     | 1"     | 1            | 150 | 70  |
| 50-200     | 1 1/4" | 1            | 150 | 70  |
| 50-200     | 1 1/2" | 1            | 150 | 70  |
| 100-300    | 1"     | 1            | 195 | 92  |
| 100-300    | 1 1/4" | 1            | 195 | 92  |
| 100-300    | 1 1/2" | 1            | 195 | 92  |
| 100-300    | 2"     | 1            | 195 | 92  |
| 150-400    | 2"     | 1            | 216 | 157 |
| 150-400    | 1 1/2" | 1            | 216 | 157 |
| 150-400    | 3"     | 1            | 216 | 157 |




| Size    | Bands<br>Thickness | Bolts Length<br>F | Bolts Thread<br>Length |
|---------|--------------------|-------------------|------------------------|
| 54-64   | 1.5                | M12*120           | 100                    |
| 60-77   | 1.5                | M12*120           | 100                    |
| 77-95   | 1.5                | M12*120           | 100                    |
| 95-119  | 1.5                | M12*120           | 100                    |
| 102-122 | 1.5                | M12*120           | 100                    |
| 120-150 | 1.5                | M12*150           | 130                    |
| 125-135 | 1.5                | M12*120           | 100                    |
| 139-160 | 1.5                | M12*120           | 100                    |
| 150-180 | 1.5                | M12*150           | 130                    |
| 151-171 | 1.5                | M12*120           | 100                    |
| 160-185 | 1.5                | M12*120           | 100                    |
| 170-195 | 1.5                | M12*120           | 100                    |
| 173-198 | 1.5                | M12*120           | 100                    |
| 195-220 | 1.5                | M12*120           | 100                    |
| 200-230 | 1.5                | M12*150           | 130                    |
| 223-248 | 1.5                | M12*120           | 100                    |
| 230-250 | 1.5                | M12*120           | 100                    |
| 250-280 | 1.5                | M12*150           | 130                    |
| 285-315 | 1.5                | M12*150           | 130                    |
| 315-340 | 1.5                | M12*120           | 100                    |
| 320-345 | 1.5                | M12*120           | 100                    |
| 330-355 | 1.5                | M12*120           | 100                    |
| 355-380 | 1.5                | M12*120           | 100                    |
| 385-400 | 1.5                | M12*120           | 100                    |
| 400-425 | 1.5                | M12*120           | 100                    |
| 410-435 | 1.5                | M12*120           | 100                    |

All the components can be substituted with equivalent or higher-class materials.

DAVINCI VALVES LTD, is constantly looking at all ways of improving our products and services related to the water, fire and industry sector and therefore we reserve the right to change, without prior notice, any of the data contained here. Please contact our Technical Sales Department for detailed advice.  
© 2018 DAVINCI VALVES LTD.

www.davincivalves.com info@davincivalves.com +34 616553797 / +86 17340168233  
18 Donqyu Street, Square One 11th Floor 1101. Jinjiang District, Chongqing, Sichuan Province, China

*"For professionals who wants more"*



DAVINCI  
VALVES™

[www.davincivalves.com](http://www.davincivalves.com)